

Two-Wheel Drive Rough Terrain Forklift

	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.									
Distinguishing mark	1.2	Manufacturer's type designation		CPCD25-XW33E-RT			CPCD35-XW33E-RT CPCD25-XW43E-RT						
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Diesel	Diesel	Diesel	Diesel	CPCD30-XW43E-RT Diesel					
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker		Seated	Seated	Seated	Seated	Seated					
ngu mar	1.5	Rated capacity/rated load	Q (kg)	2500	3000	3500	2500	3000					
Stir	1.6	Load centre distance	c (mm)	500	500	500	500	500					
	1.8	Load distance, centre of drive axle to fork	x (mm)	585	600	600	585	600					
	1.9	Wheelbase	y (mm)	1880	1880	1880							
	2.1	Service Weight	kg	4670	5120	5380	4670	1880 5120					
Weight	2.2	Axle loading, laden front/rear	kg	6050/1120	7080/1040	7800/1080	6050/1120	7080/1040					
We	2.3	Axle loading, unladen front/rear	kg	2010/2660	2300/2820	2280/3100	2010/2660	2300/2820					
	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane	0	Pneumatic	Pneumatic		Pneumatic Pneumatic Pn						
iš	3.2	Tyre size, front		12-16.5-14PR	14-17.5-14PR	14-17.5-14PR	12-16.5-14PR	14-17.5-14PR					
Jass	3.3	Tyre size, rear		27×10-12-12PR	27×10-12-12PR	27×10-12-12PR	27×10-12-12PR	27×10-12-12PR					
, t	3.5	Wheels, number front / rear (x = driven wheels)		2x/2	2x/2	2x/2	2x/2	2x/2					
Tyres, chassis	3.6	Tread, front	b10 (mm)	1250	1250	1250	1250	1250					
	3.7	Tread, rear	b ₁₁ (mm)	1200	1200	1200	1200	1200					
	4.1	Tilt of mast/fork carriage forward/backward	α/β(°)	10/12	10/12	10/12	10/12	10/12					
	4.2	Height, mast lowered	hı (mm)	2215	2350	2350 2215		2350					
}	4.3	Free lift	h ₂ (mm)	140	145	145	140	145					
	4.4	Lift	h ₃ (mm)	3000	3000	3000	3000	3000					
	4.5	Height, mast extended	h4 (mm)	4122	4142	4142	4122	4142					
	4.7	Height of overhead guard (cabin)	h6 (mm)	2390	2420	2420	2390	2420					
	4.19	Overall length	lı (mm)	4205	4220	4220	4205	4220					
Dimensions	4.20	Length to face of forks	l ₂ (mm)	2985	3000	3000	2985	3000					
	4.21	Overall width	b1(mm)	1557	1599	1599	1557	1599					
E I	4.22	Fork dimensions	s/e/I (mm)	40×122×1220	50×122×1220	50×122×1220	40×122×1220	50×122×1220					
ä	4.23	Fork carriage DIN 15 173 ISO 2328, class/type A,B	3, 6, 1 (11111)	В	B	B	В	B					
	4.24	Fork-carriage width	b₃ (mm)	1150	1150	1150	1150	1150					
	4.25	Distance between fork-arms	bs (mm)	290-1150	290-1150	290-1150	290-1150	290-1150					
	4.31	Ground clearance, laden, below mast	m ₁ (mm)	240	270	270	240	270					
	4.32	Ground clearance, centre of wheelbase	m ₂ (mm)	270	300	300	270	300					
	4.34	Aisle width	Ast (mm)	4885	4900	4900	4885	4900					
	4.35	Turning radius	Wa (mm)	2900	2900	2900	2900	2900					
	5.1	Travel speed, laden/unladen	km/h	24/26	26/28	26/28	24/26	24/26					
<u>.</u>	5.2	Lift speed, laden/unladen	m/s	0.620/0.640	0.490/0.510	0.430/0.510 0.620/0.640		0.490/0.510					
nce	5.3	Lowering speed, laden/unladen	m/s	0.500/0.440	0.500/0.450	0.500/0.450	0.500/0.440	0.500/0.450					
Performance data	5.5	Drawbar pull, laden	N	21000	22000		23000 21000						
흔히	5.7	Gradeability, laden	%	27	22	22	26	22000					
g	5.10	Service brake		Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic					
ŀ		Parking brake		Mechanical	Mechanical	Mechanical	Mechanical	Mechanical					
<u>ə</u>	7.1	Engine manufacturer/type		YANMAR 4TNE98	YANMAR 4TNE98	YANMAR 4TNE98	CUMMINS QSF2.8t3NA49						
igi	7.2	Engine power according to DIN ISO 1585	kw/r/min	42.1/2300	42.1/2300	42.1/2300	36.5/2500	36.5/2500					
Electric engine	7.3	Rated speed	N·m/r/min	196/1700	196/1700	196/1700	186/1500	186/1500					
Ē	7.4	Number of cylinders/displacement	(-)/(cm ³)	4/3319	4/3319	4/3319	4/2800	4/2800					
Ele	7.10	Battery voltage/nominal capacity	V/Ah	12/90	12/90	12/90	12/90	12/90					
	10.3	Hydraulic Tank - capacity (drain & refill)	liter	65	65	65	65	65					
Addition data	10.4	Fuel tank capacity	liter	65	65	65	65	65					





2.5-3.5t Mast:(pneumatic)

Туре	Model	Max.fork height	Overall height						Free	lift		Front O	verhang	Tilt range		Residual load capacity				
			Lowered (mm)		Extended			Without backrest		With backrest		Tronc overnang		FWD	BWD	Load Center 500mm				
					Without backrest (mm)		With backrest (mm)		(mm)		(mm)		(mm)		IWD	DWD	ISO 22	ISO 22915-2 ISO 22915-1		
		mm	2.5t	3/3.5t	2.5t	3/3.5t	2.5t	3/3.5t	2.5t	3/3.5t	2.5t	3/3.5t	2.5t	3/3.5t	(°)	(°)	2.5t	3t	2.5t	3t
Wide view mast	RTE25/35M300	3000	2215	2350	3782	3993	4122	4142	140	145	140	145	585	600	10	12	2500	3000	2500	3000
	RTE25/35M330	3300	2365	2500	4082	4293	4422	4442	140	145	140	145	585	600	10	12	2500	3000	2500	3000
	RTE25/35M350	3500	2465	2600	4282	4493	4622	4642	140	145	140	145	585	600	10	12	2500	3000	2500	2800
	RTE25/35M370	3700	2615	2700	4482	4693	4822	4842	140	145	140	145	585	600	10	12	2500	3000	2500	2600
	RTE25/35M400	4000	2815	2950	4782	4993	5122	5142	140	145	140	145	585	600	10	12	2500	3000	2100	2400
	RTE25/35M450	4500	3065	3200	5282	5493	5622	5642	140	145	140	145	585	600	10	12	2300	2500	1800	2000
Wide view full free triplex mast	RTE25/35N400	4000	2115	2300	4860	5025	5122	5269	1255	1275	933	970	495	618	10	12	2500	2900	2000	2300
	RTE25/35N430	4300	2215	2400	5160	5325	5422	5569	1355	1375	1093	1070	603	618	10	12	2400	2700	1900	2100
	RTE25/35N450	4500	2265	2450	5360	5525	5622	5769	1405	1425	1143	1120	603	618	10	12	2200	2500	1700	1900
	RTE25/35N470	4700	2365	2550	5560	5725	5822	5969	1505	1525	1243	1170	603	618	10	12	2000	2300	1400	1500
	RTE25/35N500	5000	2515	2700	5860	6025	6122	6269	1655	1675	1393	1270	603	618	6	6	1900	2100	1100	1200
	RTE25/35N550	5500	2715	2900	6360	6525	6622	6769	1855	1875	1593	1420	603	618	6	6	1500	1900	800	900
	RTE25/35N600	6000	2965	3150	6860	7025	7122	7269	2105	2125	1843	1670	603	618	6	6	1200	1600	600	700



ZHEJIANG HANGCHA IMP. &EXP. CO., LTD.

Factory site: No. 88, Donghuan Rd., Lin'an Economic Development Zone, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88132890 88926789

sales@hcforklift.com www.hcforklift.com







HANGCHA trucksconff to the European Safet Requirements.

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



Two-Wheel Drive Rough Terrain Forklift

with capacities of 2,500 to 3,500kg



The World of Hangcha

Two-Wheel Drive Rough Terrain Forklift

Hangcha 2.5~3.5t rough terrain forklifts is a tough, compact forklift with a two-wheel drive system. It is based on XF series IC forklift truck, adopt CUMMINS and YANMAR diesel engine. It is world renowned for superior performance, economy and longevity.



Reliability

- / Suspension hydraulic transmission with two forward gears and one reverse, providing higher speed and greater gradeability; Drive axle is equipped with wide-base and deep tread tires, enhanced brakes, bearings, differential with automatic locking function, as well as enhanced steering axle assembly providing ultimate traction during inclement weather conditions and rough operating surfaces.
- / Dual air filter\extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.

 Oscillating steer axle allows either wheel to step over obstacles keeping the truck and load level, high ground clearance offers greater maneuverability and keeps the truck moving in the roughest of applications.
- / The new vehicle controller integrates all electrical components, features excellent durability for temperature\water and vibration, and the oil filter/return oil filter are all work for the most demanding operation.

Environmental friendliness

- / Each model employs a specially developed engine for the optimum balance of power and superior environmental performance, the truck is in compliance with EU III and EAP III control regulation.
- / The environment friendly materials, such as non-asbestos brake shoe and new type sealing gasket, are adopted entirely to meet environmental safety. And the noise level is reduced too.

Easy maintenance

- / The cover on the Panel can be lifted up simply to check the brake fluid.
- / The two-piece design makes the floorboard easy to lift and remove for access to the power train.
- / The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.

Standard specification

- / Suspension transmission
- / Overhead gaurd
- / Suspension seat
- / Return oil filter
- / Big capacity aluminum radiator
- / Air filter
- / Rear working light
- / Warning lamp
- / Cover for tilt cylinder
- / Net cover of radiator
- / Reversing assist grip
- / Wider fork carriage
- / Wider load backrest
- / LED light

Options

- / Cabin
- / Heater
- / Front window
- / L/R mirror
- / Extinguisher
- / Customer painting
 / OPS system
- / Sparkle arrester
- / Purified exhaust system
- / Auxiliary hydraulic valve
- / Front working light
- / Triplex wide view free-lift mast
- / Special forks
- / Weigher system
- / Attachments



ne new efficiency lighting system nploys LED illuminant and new type flector to reduce energy consumption, nprove significantly illumination erformance and prolong work time



Optimized designing structure to offer a good visibility and easy entrance of the nallet



The new designed steering wheel\ new brake system and the easy-to-operate levers provide total bandling operation.



The easy-to-open hook provides quaccess to the engine compartment

Productivity

/ The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.

Comfortable operation

- / In developing the rough terrain forklift, comfort and easy operation is always considered, for example, improved vibrating levels, compound engine damper and full floating seat and cabin are all applied. Comfortable also contribute to increased productivity and reduced the noise.
- / The extra foot space is provided to reduce operator fatigue significantly, non-slip step makes getting in and out easy and safe.
- / The new design mast provides broad forward visibility due to the longer distance between inside mast.

